
	ITEM	QTY. -041	P/N	DESCRIPTION
<u>Ĉ</u>	1	х	D4866-041	AFT LEG ASSEMBLY, LH
	2	1	D4866-1	STRUT
	3	1	D4870-1	END FITTING, SMALL
	4	1	D4870-3	END FITTING, LARGE
<u> </u>	5	4	HL32PB5-12	HI-LOK PIN
	6	4	HL86-5	HI-LOK COLLAR



D4866-041 AFT LEG ASSEMBLY, LH (EQUIVALENT TO BELL P/N 206-063-105-001)

8

2) FINISH: N/A
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY PER QSI 044 6.8
7) WEIGHT: 0.76 lbs


7) WEIGHT: 0.76 lbs
8) ALIGN PILOT HOLES IN D4866-1 WITH PILOT HOLES IN D4870-1 & D4870-3.
DRILL OUT EACH HOLE USING A P/N 13-SB65 (0.125) PILOTED DRILL.
REAM EACH HOLE USING P/N 31-219 (Ø 0.1610) REAMER, USING DART TOOL SETUP DT9962
9) INSTALL PIN/COLLAR AND END FITTING WITH HYSOL EA934NA OR MAGNOBOND 6398 ADHESIVE WHILE STILL WET
10) ASSEMBLE PER DART TOOL DT9962
11) INSTALL HL32PB5-12 HI-LOK IN ORIENTATION SHOWN

REV.	DESCRIPTION	BY	DATE			
Α .	NEW ISSUE	RF	13.09.16			
В	REVISE NOTES 6) & 9) (ZN A8-1, A8-3); ADDED BELL P/N	RF	14.04.08			
С	HL32PB5-12 WAS HL20PB5-12 (ZN D4-1, D4-3); REVISE NOTE 6) (ZN A8-5, A8-6); REVISED PART DESCRIPTION RF (ZN B4-1, B4-2, B4-3, B4-4)					


DESIGN	RF	DART AEROSPA	CE LTD
DRAWN VS		HAWKESBURY, ONTARIO, CANADA	
CHECKED HS		DRAWING NO.	REV. C
MFG. APPR.	JLM	D4866	SHEET 1 OF 6
APPROVED	HS ",	TITLE	SCALE
DE APPR.	DS -	LEG ASSEMBLY	NTS
DATE		COPYRIGHT © 2013 BY DART AEROSPACE LTD	

14.06.24

APPROVED



	ITEM	QTY. -042	P/N	DESCRIPTION
<u>⟨c</u>	1	X	D4866-042	AFT LEG ASSEMBLY, RH
	2	1	D4866-2	STRUT
	3	1	D4870-1	END FITTING, SMALL
	4	1	D4870-3	END FITTING, LARGE
⟨Ĉ\	5	4	HL32PB5-12	HI-LOK PIN
	6	4	HL86-5	HI-LOK COLLAR



D4866-042 AFT LEG ASSEMBLY, RH (EQUIVALENT TO BELL P/N 206-063-105-002)

SCALE

1) MATERIAL: N/A

2) FINISH: N/A

3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED 4) UNITS: INCHES UNLESS OTHERWISE NOTED

5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.8

7) WEIGHT: 0.76 lbs
8) ALIGN PILOT HOLES IN D4866-2 WITH PILOT HOLES IN D4870-1 & D4870-3.
DRILL OUT EACH HOLE USING A P/N 13-SB65 (0.125) PILOTED DRILL.

REAM EACH HOLE USING P/N 31-219 (\$\phi 0.1610)\$ REAMER, USING DART TOOL SETUP DT9963


9) INSTALL PIN/COLLAR AND END FITTING WITH HYSOL EA934NA OR MAGNOBOND 6398 ADHESIVE WHILE STILL WET

10) ASSEMBLE PER DART TOOL DT9963

11) INSTALL HL32PB5-12 HI-LOK IN ORIENTATION SHOWN


DESIGN DART AEROSPACE LTD DRAWN VS APPROVED HAWKESBURY, ONTARIO, CANADA HS DRAWING NO. **CHECKED** REV. C D4866 MFG. APPR. JLM SHEET 3 OF 6 TITLE **APPROVED** HS LEG ASSEMBLY DE APPR. DS COPYRIGHT © 2013 BY DART AEROSPACE LTD
THIS DOCUMENT IS PRIVATE AND COMPIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION OT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON DATE 14.06.24

3



. 2

3



DRAWN VS APPROVED HAWKESBURY, ONTARIO, CANADA DRAWING NO. HS **CHECKED** D4866 MFG. APPR. JLM TITLE **APPROVED** HS DS LEG ASSEMBLY DE APPR. DATE 14.06.24

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION TO BE LICED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSO

REV. C

SHEET 5 OF 6

8) LIQUID PENETRANT INSPECT PER QSI 038 6.1.1 (ASTM E1417 LEVEL 2)

7) WEIGHT: 0.36 lbs

3

